

## Specification for “T-Line” Toilet Cubicle system – Ceiling Hung Module

Providing & fixing of Toilet cubicle/ Shower cubicle / Change room of T-Line make, Ceiling Hung module with 12mm compact board, aluminium SS finish sections & SS 304 grade hardware, height 2400mm / 2700mm including bottom gap of 150mm.

<b>Cubicle Size:</b>	1000mm(W) x 1500mm(D) x 2400mm/2700mm(H)
<b>Door Size:</b>	600mm(W) x 1800mm(H)
<b>Divider Size:</b>	1500mm(W) x 1800mm(H)
<b>Front panel Size:</b>	As per drawing x 2400/2700mm(H)
<b>Over All height:</b>	2400 / 2700mm including 150mm bottom gap

Note: The above size & height is standard, it can be customized as per the site requirement.

**Panels:** High-Pressure Laminate (HPL) Compact board made from layers of Kraft paper core treated with phenolic resin and top design paper treated with melamine resin compressed under high temperature and pressure & having density >1400 kg/cm<sup>3</sup> and comply with EN438, IS-2046 standards & BS 476/97 fire standards. The board is to be antifungal, antibacterial and resistant to impact, scratch, heat, chemical & water. The divider panel is to be one continuous panel without any joints, the front panel & door are to be cut to the required width & height as per the drawing.

**Section:** All sections to be of Aluminium SS anodized finish, the divider to be fixed to the wall using “U” profile, and the front panel to be fixed to the divider with SS 304 “L” brackets. All front panels to be fixed above the false ceiling with the help of Aluminium / MS framing for stability & rigidity. 7mm deep & 12mm wide rebate grooves are cut into the front panel and door for door closing. 2mm thick rubber liner to be pasted on the front panel rebate edge for door banging noise reduction. All screws used in fixing to be of SS 304 grade. “L” bracket to be provided at corners wherever needed.

**Hardware:** All cubicles are equipped with the following SS 304 Grade hardware.

- Indicator Lock - Lock with a red-green occupancy vacancy sign to be fixed on the Front Panel.
- Handle - To be fixed on both sides of the door.
- Coat Hook - To be fixed on the inside of the door, 1 no. each.
- Hinges - To be fixed on the inside, between door & front, 3 no. per door.

Note: Cubicle in 18mm thickness available for high traffic areas & combination of 18mm front & door panel & 12mm divider also available.

**Mode of measurement:** Per cubicle basis.

