

## Specification for "T-Line" Toilet Cubicle system – Center Leg Rebate Module

Providing & fixing of Toilet cubicle/ Shower cubicle / Change room of **T-Line** make, Centre Leg module with 12mm compact board, SS 304 sections & SS 304 / SS 316 grade hardware, height 2100mm including bottom gap 135 to 150mm.

Cubicle Size:	1000mm(W) x 1500mm(D) x 2100mm(H)
Door Size:	600mm(W) x 1920mm(H)
<b>Divider Size:</b>	1500mm(W) x 1920mm(H)
Front panel Size:	As per drawing x 1950mm(H)
<b>Over All height:</b>	2100mm including 135-150mm bottom leg

Note: The above size & height is standard, it can be customized as per the site requirement.

**Panels:** High-Pressure Laminate (HPL) Compact board made from layers of Kraft paper core treated with phenolic resin and top design paper treated with melamine resin compressed under high temperature and pressure & having density >1400 kg/cm3 and comply with EN438, IS-2046 standards & BS 476/97 fire standards. The board is to be antifungal, antibacterial and resistant to impact, scratch, heat, chemical & water. The divider panel is to be one continuous panel without any joints, the front panel & door are to be cut to the required width & height as per the drawing.

Section: All sections to be of SS 304 Grade, the divider to be fixed to the wall using "U" profile, and the front panel to be fixed to the divider with "U" profile. One Leg support to be fixed on the divider at the bottom. Top rail to be fixed on top of the boards connecting all front panels in line for stability & rigidity. 7mm deep & 12mm wide rebate grooves are cut into the front panel and door for door closing. 2mm thick rubber liner to be pasted on the front panel rebate edge for door banging noise reduction. All screws used in fixing to be of SS 304 grade. "L" profile to be provided at corners wherever needed.

Hardware:All cubicles are equipped with the following SS 304 / SS 316 Grade hardware.Indicator Lock -Lock with a red-green occupancy vacancy sign to be fixed on the Front Panel.Handle -To be fixed on both sides of the door.Coat Hook -To be fixed on the inside of the door, 1 no. each.Hinges -To be fixed on the inside, between door & front, 3 no. per door.Leg -To be fixed on the Divider at the bottom, 1 no. each.

Note: Cubicle in 18mm thickness available for high traffic areas & combination of 18mm front & door panel & 12mm divider also available.

## Mode of measurement: Per cubicle basis.







707, 7<sup>th</sup> Floor, 765 Fly Edge Building, Kora Kendra Junction, S.V. Road Borivali (W) Mumbai-400092 Tel: +91 22 2805 2157 / 58 / 59. Email: info@tline.in, innersp@gmail.com