

Specification for “T-Line” Locker Range

Supply of **T-Line** Locker system with 15mm thick High Density PVC (HDP) board, SS fittings & hardware.

Panels: 15mm thick HDP board panel and 1mm thick HPL sheet of chosen laminate colour on the outer side with 1mm rigid pvc beading on all sides of the door panel. The panel to be antifungal, antibacterial and resistant to water, corrosion and termites.

Specifications:

Side, Top & Bottom Panel: Made from 15mm thick HDP & 1mm laminate on one side - outer side.

Divider Panel & shelf: Made from 15mm thick HDP.

Door: Made from 15mm thick HDP and 1mm thick laminate on front side, 1mm thick edge beading on all four sides of the doors.

Back side Panel: Made from 8 mm thick HDP board.

Stand: 100mm high stand or skirting made from 15mm thick HDP and 1 mm laminated on the outer side.

Dimensions:

Size of 1 standard unit: 1200mm width, 1800mm height, 400mm depth with 100mm stand, Total height 1900mm.

Locker Compartment: 1 Standard unit can be divided in several compartments as per the requirement of the customer like 4, 8, 12, 16, 24 (300 x 300, 300 x 450, 300 x 600, 300 x 900, 300 x 1800mm).

Note: The locker can be customized, as per the requirement of the customer and as per the available space at the site.

Hardware: All lockers are equipped with the following SS 304 Grade hardware.

Lock - CAM Key-lock with master key.

Handle - SS handle / Knob.

Hinges - SS 304 hinges.

Note: Options for numeric locks and handle designs available as per requirement.

Mode of measurement: Per locker basis.

