

## Specification for “T-Line” Toilet Cubicle system – Only Door

Providing & fixing of Toilet cubicle/ Shower cubicle / Change room of **T-Line** make, Only Door with 12mm compact board, SS 304 grade hardware & Aluminium SS finish profile, height 1950mm including bottom gap 50 to 150mm.

**Door Size:** 600mm(W) x 1800mm(H)  
700mm(W) x 2100mm(H)

**Top & Bottom Gap:** 50mm - 150mm

Note: The above size & height is standard, it can be customized as per the site requirement.

**Panels:** High-Pressure Laminate (HPL) Compact board made from layers of Kraft paper core treated with phenolic resin and top design paper treated with melamine resin compressed under high temperature and pressure & having density >1400 kg/cm<sup>3</sup> and comply with EN438, IS-2046 standards & BS 476/97 fire standards. The board is to be antifungal, antibacterial and resistant to impact, scratch, heat, chemical & water.

**Section:** The “Door profile” to be of Aluminium SS anodized and to be fixed to the brick wall on both sides. Silicon rubber to be inserted in the “Door profile” of the door opening end for reducing the door banging noise. All screws used in fixing to be of SS 304 grade. A rubber “end cap” to be fixed on the top & bottom ends of the door profile.

Note: Powder coated section also available as per requirement

**Hardware:** All cubicles to be equipped with the following SS 304 Grade hardware.  
Indicator Lock - Slider lock with a red-green occupancy vacancy sign to be fixed on Front Panel.  
Handle - To be fixed on both sides of the door.  
Coat Hook - To be fixed on the inside of the door, 1 no. each.  
Hinges - To be fixed on the inside, between door & front, 3 no. per door.  
Rubber end cap- To be fixed at the top & bottom of door profile, 4 no. per door.

Note: Hardware in Nylon Polyamide Grade 6 available as per requirement.

Note: Door in 18mm thickness available for high traffic areas.

**Mode of measurement:** Per cubicle basis.

