

### Specification for “T-Line” Toilet Cubicle system – SS Grand Shoe Module

Providing & fixing of Toilet cubicle/ Shower cubicle / Change room of T-Line make, SS Grand Shoe Module with 12mm compact board, SS 304 sections & SS 304 / SS 316 grade hardware and SS 316 shoebox, height 2100mm including 100mm bottom shoe.

<b>Cubicle Size:</b>	1000mm(W) x 1500mm(D) x 2100mm(H)
<b>Door Size:</b>	600mm(W) x 1950mm(H)
<b>Divider Size:</b>	1500mm(W) x 1950mm(H)
<b>Front panel Size:</b>	As per drawing x 2100mm(H)
<b>Over All height:</b>	2100mm including 100mm bottom shoe

Note: The above size & height is standard, it can be customized as per the site requirement.

**Panels:** High-Pressure Laminate (HPL) Compact board made from layers of Kraft paper core treated with phenolic resin and top design paper treated with melamine resin compressed under high temperature and pressure having & density >1400 kg/cm<sup>3</sup> and comply with EN438, IS-2046 standards & BS 476/97 fire standards. The board is to be antifungal, antibacterial and resistant to impact, scratch, heat, chemical & water. The divider panel is to be one continuous panel without any joints, the front panel & door are to be cut to the required width & height as per the drawing.

**Section:** All sections (U, h, L, top rail) to be of SS 304 Grade, the divider to be fixed to the wall using “U” profile, and the front panel to be fixed to the divider with “U” profile. Top rail to be fixed on top of the boards connecting all front panels in line for stability & rigidity. SS 316 “shoe profile” to be fixed on the Front panel at the bottom with “L shoe” bracket. “h” profile to be provided on both ends of the front panel for door closing. Silicon rubber to be inserted in the “h” profile for reducing the door banging noise. All screws used in fixing to be of SS 304 grade. “L” profile to be provided at corners wherever needed.

**Hardware:** All cubicles are equipped with the following SS 304 / SS 316 Grade hardware.

Indicator Lock -	Lock with a red-green occupancy vacancy sign to be fixed on the Front Panel.
Handle -	To be fixed on both sides of the door.
Coat Hook -	To be fixed on the inside of the door, 1 no. each.
Hinges -	To be fixed on the inside, between door & front, 3 no. per door.
Shoe profile -	To be fixed on the Front panel at the bottom. (For shower cubicles shoe also in divider panels to prevent water flow into adjacent cubicles)

Note: Cubicle in 18mm thickness available for high traffic areas & combination of 18mm front & door panel & 12mm divider also available.

Note: Rebate edge on door for seamless & flushed finish available on requirement.

**Mode of measurement:** Per cubicle basis.

